

E125
Eiger Petit Engineered Collection
Oak Rustic Lacquered



Product Description

Giving the stability and strength of the Eiger Collection with unbeatable value the Eiger Petit offers a versatile and durable multi-ply with the character of a traditional solid floor. Multi Layered hardwood with random sized boards and thick top layers, the Eiger Petit Collection is bursting with character floors. The 125mm x 6mm rustic oak top layer is smooth sanded and coated with up to 6 coats of UV cured aluminum oxide lacquer. The floor is scratch resistant and ideal for high traffic area where easy maintenance is required.

Product Information

USAGE	Commercial and Residential Applications
Product Code	E125
Name	Eiger Petit Oak Rustic Lacquered
Dimensions	125 x 18 x Random mm
Board Type	Multi-Ply Engineered hardwood board with tongue & groove profile
Pattern	1 Strip Micro Bevelled Plank
Pack Size	2.2m ² with random length boards
Top layer	5 mm Rustic European Oak
Timber Grade	CD Rustic Grade
Surface	Lacquered
Suitable for Underfloor Heating	Yes (temperature of top face must not exceed 27°C /See fitting guide)
Guarantee	35 Year Domestic Guarantee (see website for details)
Commercial Guarantee	3 Year Commercial Guarantee (see website for details)

© This technical data sheet was written by V4 Woodflooring Ltd. Greenbays Park Carthouse Lane, Horsell, Surrey GU21 4YP. At the time of writing and publication of sheet, all the information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs used in this sheet are intended only as illustrations. No rights can be derived from them.

Grading Criteria - CD Rustic

V4 Woodflooring is chosen for its natural beauty, therefore grading criteria is always an approximation as every piece of timber is different. If further selection is needed please allow for extra material upon installation.

Maximum Size of Sound Knots	50 mm Diameter (approx')
Maximum Size of Filled Knots	30 mm Diameter (approx')
Filled Defects	Allowed
Filler Type	Black and dark brown filler
Sap Wood	Allowed
End Checks	Not Allowed
Heart Wood	Allowed
Insect Damage	Not Allowed
Colour Variation	Allowed
Small Shakes	Allowed
Ingrown Bark	Not Allowed
Grain Variation	Allowed

General Data

Country of manufacture	China
European Timber Regulation	Full documented evidence of legality of timber
FSC®	FSC® 100% Certification Available for Project Enquires
PEFC®	Not available with this product
JANKA HARDNESS RATING	Oak 1360 lbf (6000N)
SLIP RESISTANCE	EN 1339 (test result USRV 100)
EUROPEAN REACTION TO FIRE CLASSIFICATION	EN 13501-1 (test result: Dn - S1)
THERMAL CONDUCTIVITY	EN 12524 (Test result: 0.16W/mK)
RELEASE OF FORMALDEHYDE	EN 717-1 (Test result \leq 0.012mg/m3)
STAIN RESISTANCE	Good resistance in conjunction with initial oil maintenance and ongoing proper maintenance
ACCOUSTIC PROPERTIES	Contact V4 Woodflooring Technical Department

© This technical data sheet was written by V4 Woodflooring Ltd. Greenbays Park Carthouse Lane, Horsell, Surrey GU21 4YP. At the time of writing and publication of sheet, all the information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs used in this sheet are intended only as illustrations. No rights can be derived from them.

Installation Method

V4 Woodflooring® should be fitted in accordance with our installation guides by experienced flooring installers for more information visit www.v4woodflooring.co.uk.

Fully Bonded	Yes
Secret Nailed	Yes
Floated on Underlay	Yes
Over Underfloor heating	Yes Temperature of top surface should not exceed 27°C

Cleaning & Maintenance - Domestic Schedule

Floors should be kept clean and free from dust and grit and furniture should be protected to avoid unnecessary wear and damage. All external doors should have mats to collect grit, fitted inside and out.

RECOMMENDED PRODUCTS*	REGULAR	MONTHLY	6 MONTHLY
WOOD'S GOOD LACQUER SOAP SPRAY	√		
WOOD'S GOOD LACQUER SOAP MOP APPLIED		√	
WOOD'S GOOD PARQUET CARE			√

Cleaning & Maintenance - Commercial Schedule

Floors should be kept clean and free from dust and grit and furniture should be protected to avoid unnecessary wear and damage. All external doors should have mats to collect grit, fitted inside and out.

RECOMMENDED PRODUCTS*	REGULAR	MONTHLY	6 MONTHLY
WOOD'S GOOD LACQUER SOAP SPRAY			
WOOD'S GOOD LACQUER SOAP MOP APPLIED	√		
WOOD'S GOOD PARQUET CARE		√	

* Visit www.v4woodflooring.co.uk for detailed advice on using the above products.

© This technical data sheet was written by V4 Woodflooring Ltd. Greenbays Park Carthouse Lane, Horsell, Surrey GU21 4YP. At the time of writing and publication of sheet, all the information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs used in this sheet are intended only as illustrations. No rights can be derived from them.